

PRIORI T2



High light output and energy savings in a low profile fixture with a modular design.

Performance

- Warm White light with 90 CRI mimics the look of incandescent but without the heat
- Modular design allows flexibility and easy installation
- Low profile housing hides easily – less than 1" high
- Long life fluorescent T2 lamps are rated for 10,000 hours

Construction

- Steel housing with powder coat finish
- Prismatic tempered glass lens diffuses light
- Magnetic closure secures cover without clips or tabs that can bend or break

Installation

- Mount to underside of shelf or cabinet, at the leading edge, for best performance
- Modular design with hardwire junction boxes, power cords and linking cables sold separately offers maximum flexibility and optimal fixture placement
- Quick release clip provides tool-free access to wiring compartment saving time for hardwire installations
- Captive screw design speeds installation



Specifications

Series	043T
Input voltage	120V AC, 60Hz
Color temperature	3000K
CRI	90+
Wattage	6W / 8W / 13W / 18W / 24W
Lumens	See individual product
Maximum run	600 watts
Beam angle	120°
Dimming	Non-dimming
Housing	Cold rolled steel
Lens	Prismatic tempered glass
Rating	c/UL/us Listed, dry locations
Dimensions	3-3/4"W x 15/16"H x Length
Power input	Hardwire, modular or plug-in
Mounting	Captive screws
Linking	Via 043A linking cables
Lamp type	T2 with axial base, 3000K
Rated life	10,000 hrs

Building a System

Determine Layout:

- Determine the quantities and lengths of fixtures needed.
- Determine power input:
 1. Hardwire via knockouts
 2. Modular with junction box
 3. Plug-in

Select Power Input Accessories:

1. Hardwire via knockouts: no additional accessories needed
2. Modular with junction box: use ALC-BOX with 12" jumper
3. Plug-in: use ALC-PC6, one per fixture or one for first fixture and link subsequent

Select Linking Accessories:

1. Direct end-to-end: no additional accessories needed
2. Linking cables: Choose 6", 12", 24" or 36" jumpers (043A linking cables)

Priori T2



Priori T2 - Dark Bronze

043T-10-DB

10-1/4" / 6W / 228Lm

043T-14-DB

14-1/2" / 8W / 304Lm

043T-22-DB

22-1/2" / 13W / 494Lm

043T-28-DB

28-1/2" / 18W / 684Lm

043T-32-DB

32-1/2" / 24W / 912Lm

Priori T2 - Brushed Steel

043T-10-BS

10-1/4" / 6W / 228Lm

043T-14-BS

14-1/2" / 8W / 304Lm

043T-22-BS

22-1/2" / 13W / 494Lm

043T-28-BS

28-1/2" / 18W / 684Lm

043T-32-BS

32-1/2" / 24W / 912Lm

Priori T2 - White

043T-10-WH

10-1/4" / 6W / 228Lm

043T-14-WH

14-1/2" / 8W / 304Lm

043T-22-WH

22-1/2" / 13W / 494Lm

043T-28-WH

28-1/2" / 18W / 684Lm

043T-32-WH

32-1/2" / 24W / 912Lm

Priori T2 Accessories



043J-WH (White)

043J-BR (Bronze)

Hardwire junction box for PRIORI fixtures
7-3/8"L x 2-1/8"W x 1"H
Includes 12" extension and two 3/8" cable connectors
c/UL/us Listed, dry



043A-PC6-WH (White)

043A-PC6-BK (Black)

6ft power cord for PRIORI fixtures
120V AC grounded plug, 3-wire grounded molex connector
c/ETL/us Listed, dry



043T-F06/30 6 watt / 3000K / 90CRI

043T-F08/30 8 watt / 3000K / 90CRI

043T-F13/30 13 watt / 3000K / 90CRI

043T-F18/30 18 watt / 3000K / 90CRI

043T-F24/30 24 watt / 3000K / 90CRI

120V T2 fluorescent replacement lamp
10,000hr rated life



043A-6-EX-BK 6"

043A-12-EX-BK 12"

043A-24-EX-BK 24"

043A-36-EX-BK 36"

Jumper (linking) Cables for PRIORI fixtures
c/UL/us Listed, dry



043A-6-EX-WH 6"

043A-12-EX-WH 12"

043A-24-EX-WH 24"

043A-36-EX-WH 36"

Jumper (linking) cables for PRIORI fixtures
c/UL/us Listed, dry