

Steel EMT Compression Connectors and Couplings

6000S Series Couplings

Features

- Concretetight.

Standard Materials

- Steel Body and Nut.

Standard Finish


- Zinc Plated

Third Party Certification

- UL Listed: E-14815 (1/2" to 2")
- UL Listed: E-14816 (2-1/2" to 4")
- Listed Concretetight 1/2" through 4".

Applicable Third Party Standards

- UL 514B
- CSA Standard C22.2 No. 18
- NEMA FB-1
- Federal Spec. W-F-408E



Type 6050S — Type 6400S

| Trade Size (Inches) | Catalog Number | Dimension in Inches | | Wt. Lbs. Per 100 | Ctn. Qty. | Std. Pkg. |
|---------------------|----------------|---------------------|-----------|------------------|-----------|-----------|
| | | Body Length | Max. Dia. | | | |
| 1/2 | 6050S | 1-3/8 | 27/32 | 19 | 25 | 250 |
| 3/4 | 6075S | 1-1/2 | 1-3/8 | 25 | 20 | 200 |
| 1 | 6100S | 1-21/32 | 1-5/16 | 39 | 20 | 100 |
| 1-1/4 | 6125S | 2-1/2 | 1-11/16 | 88 | 5 | 25 |
| 1-1/2 | 6150S | 2-1/2 | 1-15/16 | 104 | 5 | 25 |
| 2 | 6200S | 2-1/2 | 2-3/8 | 149 | 2 | 10 |
| 2-1/2* | 6250S | 4-1/4 | 3-1/8 | 240 | — | 10 |
| 3* | 6300S | 4-1/2 | 3-3/4 | 350 | — | 5 |
| 3-1/2* | 6350S | 4-3/4 | 4-1/4 | 475 | — | 5 |
| 4* | 6400S | 5 | 4-3/4 | 600 | — | 5 |

* Rated for steel EMT, Aluminum and steel RMC, and steel IMC.

7000S Series Connectors

Features

- Male hub threads NPS.
- Available with insulated throat.
- Concretetight.
- Insulated throat connector rated 90°C.

Standard Materials

- Steel Body and Nut.

Standard Finish


- Zinc Plated

Third Party Certification

- UL Listed: E-14815 (1/2" to 2")
- UL Listed: E-14816 (2-1/2" to 4")
- Listed Concretetight 1/2" through 4".

Applicable Third Party Standards

- UL 514B
- CSA Standard C22.2 No. 18
- NEMA FB-1
- Federal Spec. W-F-408E



Type 7050S — Type 7400S

| Trade Size (inches) | Catalog Number | Insulated Throat Catalog Number | Dimensions in Inches | | | Wt. Lbs. Per 100 | Ctn. Qty. | Std. Pkg. |
|---------------------|----------------|---------------------------------|----------------------|----------|---------------|------------------|-----------|-----------|
| | | | Body Length | Max Dia. | Thread Length | | | |
| 1/2 | 7050S | 7050ST | 1-1/8 | 1-1/16 | 3/8 | 15 | 25 | 250 |
| 3/4 | 7075S | 7075ST | 1-1/32 | 1-1/4 | 7/16 | 21 | 25 | 250 |
| 1 | 7100S | 7100ST | 1-1/4 | 1-9/16 | 7/16 | 32 | 20 | 200 |
| 1-1/4 | 7125S | 7125ST | 1-13/16 | 2 | 9/16 | 72 | 5 | 25 |
| 1-1/2 | 7150S | 7150ST | 2 | 2-3/16 | 9/16 | 85 | 5 | 25 |
| 2 | 7200S | 7200ST | 2-1/4 | 2-11/16 | 11/16 | 124 | 2 | 10 |
| 2-1/2* | 7250S | 7250ST | 2-3/8 | 3-11/32 | 7/8 | 160 | — | 10 |
| 3* | 7300S | 7300ST | 2-7/8 | 4 | 7/8 | 265 | — | 5 |
| 3-1/2* | 7350S | 7350ST | 3 | 4-1/2 | 1 | 425 | — | 5 |
| 4* | 7400S | 7400ST | 3-3/16 | 5-1/16 | 1 | 600 | — | 5 |

* Rated for steel EMT, Aluminum and steel RMC, and steel IMC.