

Blackburn®

Service Wedge Clamps
T&B Catalog Number:



UPC Number:
Status:
Description:

W20-1
 78378633202
 Active

Aluminum Service Entrance Wedge Clamp and Slider for Wire Range: 1/0-4 ASCR, 1/0-4 AAAC, 2/0 Str.-2 Sol. , Color Code Blue

Features

Drop wire may be cut to exact length to adjust drop wire sag. This also saves the conductor.

Can be attached to bare neutral at any point in the span.

Versatile use. Flexible and rigid bails grip ASCR, AAC and AAAC conductors.

General

Style	W - Aluminum Service Wedge Clamp
Material	Aluminum
Conductor Range - ASCR	1/0-4
Conductor Range - AL	2/0 Str.-2 Sol.
Conductor Range AAAC	1/0-4
Color Code	Blue
Typical Tensile Values - Conductor	1/0 6/1 ACSR
Tensile Value (LB.)	1,800

Dimension Information

Length (inches)	12 1/2
D (inches)	2 3/8 flex.

Packaging

Package in Units	50
T&B Sold in UOM	Each
T&B Weight Per UOM	23.7 lbs. per 100

Certifications

RoHS Compliance	Yes
-----------------	-----

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
 www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email:techsupport@tnb.com

Blackburn®

Service Wedge Clamps

T&B Catalog Number:



W20-1

UPC Number:

78378633202

Status:

Active

Description:

Aluminum Service Entrance Wedge Clamp and Slider for Wire Range: 1/0-4 ASCR, 1/0-4 AAAC, 2/0 Str.-2 Sol. , Color Code Blue

Features

Drop wire may be cut to exact length to adjust drop wire sag. This also saves the conductor.

Can be attached to bare neutral at any point in the span.

Versatile use. Flexible and rigid bails grip ASCR, AAC and AAAC conductors.

General

Style	W - Aluminum Service Wedge Clamp
Material	Aluminum
Conductor Range - ASCR	1/0-4
Conductor Range - AL	2/0 Str.-2 Sol.
Conductor Range AAAC	1/0-4
Color Code	Blue
Typical Tensile Values - Conductor	1/0 6/1 ACSR
Tensile Value (LB.)	1,800

Dimension Information

Length (inches)	12 1/2
D (inches)	2 3/8 flex.

Packaging

Package in Units	50
T&B Sold in UOM	Each
T&B Weight Per UOM	23.7 lbs. per 100

Certifications

RoHS Compliance	Yes
-----------------	-----

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com