

30 Amp Wetguard Locking Devices

3-Pole, 4-Wire • 4-Pole, 4-Wire • 4-Pole, 5-Wire

Amp	Volt	NEMA Configuration	Plug IP69K	Plug Cap	Connector IP69K	Connector Cap	Single Outlet	Duplex Outlet	Single Inlet	Connector mates with Inlet	Single Receptacle	Receptacle Cover with Gasket	
Locking 3-Pole, 4-Wire Devices													
30	125/250	L14-30		28W74 ‡	28W*	29W74 ‡	50W54*	99W74-S	---	68W74	78W74-C	27CM-10	60W05*
30	3Ø 250	L15-30		28W75 ‡	28W*	29W75	50W54*	99W75-S	---	68W75	78W75-C	27CM-20	60W05*
30	3Ø 480	L16-30		28W76* ‡	28W*	29W76* ‡	50W54*	99W76-S	---	68W76	78W76-C	2730	60W05*
30	3ØY 600	L17-30		28W77	28W*	29W77	50W54*	99W77-S	---	68W77	78W77-C	2740	60W05*
Locking 4-Pole, 4-Wire Devices													
30	3ØY 120/208	Non-NEMA		28W09	28W*	29W09	50W54*	99W09-S	---	68W09	78W09-C	3430	60W05*
Locking 4-Pole, 5-Wire Devices													
30	3ØY 120/208	L21-30		28W81	28W*	29W81	50W54*	99W81-S	---	68W81	78W81-C	2810	60W05*
30	3ØY 277/480	L22-30		28W82	28W*	29W82	50W54*	99W82-S	---	68W82	78W82-C	2820	60W05*
30	3ØY 347/600	L23-30		28W83	28W*	29W83	50W54*	99W83-S	---	68W83	78W83-C	2830	60W05*

Plugs & Connectors need caps attached in order to achieve IP69K rating.
NEMA configuration diagrams represent plug blade configuration.

* Available in black. To order, add "-B" suffix to catalog number.
‡ Replacement interior available. To order, add "-IN" to catalog number (Ex: 28W76-IN).