

Drop-In Anchor Type Non-Flange

---

Anchor Material Steel

---

Fastener Finish Zinc Plated

---

Anchor Thread Size 1/2"-13

---

Anchor Dia. 5/8 in

---

Anchor Length 2 in

---

Thread Depth 13/16 in

---

Bolt Dia. 1/2 in

---

Drill Bit Size 5/8 in

---

Min. Hole Depth 2 in

---

Installation Turns Until Set Tool Shoulders On Anchor Lip

---

Allowable Shear (Lbs.) 1792 @ 2500 psi Concrete

---

Ultimate Shear in 3000 PSI Concrete (Lb.) 7,280 lb

---

Ultimate Shear in 4000 PSI Concrete (Lb.) 7,505 lb

---

Allowable Tension (Lbs.) 907 lb @ 2500 psi

---

Ultimate Tension (Lbs.) 3630 @ 2500 psi

---

Ultimate Tension in 3000 PSI Concrete (Lb.) 3,815 lb

---

Ultimate Tension in 4000 PSI Concrete (Lb.) 4,190 lb

---

Drive Tools

Powers System Maul Set Tool; SMART DI+ System With a Hammer Drill

---

Agency Compliance

FM Global (Factory Mutual) Report # 3040746, Underwriters Laboratories (UL Listed) File # EX1289(N)

---

Meets/Exceeds FM Global; UL Listed

---

UNSPSC 31161502

---

Country of Origin China (subject to change)

---