

C2SS2-10B-20



SELECTOR SWITCH#C2SS2-10B-20

General Information

| | |
|-----------------------|----------------------------------------------------------------------------------------------------------|
| Extended Product Type | C2SS2-10B-20 |
| Product ID | 1SFA619201R1026 |
| EAN | 7320500245859 |
| Catalog Description | SELECTOR SWITCH#C2SS2-10B-20 |
| Long Description | Compact Selector Switch - 2-pos Fixed A&C - Short handle - Black - Non-illuminated - Black plastic - 2NO |

Ordering

| | |
|------------------------|---------------|
| EAN | 7320500245859 |
| Minimum Order Quantity | 10 piece |
| Customs Tariff Number | 8536501999 |

Dimensions

| | |
|----------------------------|----------|
| Product Net Width | 0.030 m |
| Product Net Height | 0.030 m |
| Product Net Depth / Length | 0.072 m |
| Product Net Weight | 0.024 kg |

Container Information

| | |
|--------------------------------|----------|
| Package Level 1 Units | 10 piece |
| Package Level 1 Width | 0.1 m |
| Package Level 1 Height | 0.03 m |
| Package Level 1 Depth / Length | 0.1 m |
| Package Level 1 Gross Weight | 0.024 kg |
| Package Level 2 Units | 10 |

Environmental

| | |
|-------------------------|-----------------------------------------------------------------|
| Ambient Air Temperature | Storage -30 ... +85 °C Operation -25 ... +70 °C |
| RoHS Status | Following EU Directive 2002/95/EC August 18, 2005 and amendment |

Additional Information

| | |
|--------------------------------------------------|----------------------------------------------|
| Actuator Type | Short handle |
| Bezel Material | Black plastic |
| Block | 2NO |
| Color | Black |
| Degree of Protection | Front IP69K Terminals IP20 |
| Function | Maintained |
| Illumination | Non-illuminated |
| Maintained Positions | A, C |
| Mechanical Durability | 0.5 million |
| Number of Auxiliary Contacts NO | 2 |
| Product Main Type | C2SS2 |
| Product Name | Selector Switch |
| Product Range | Compact |
| Product Type | C2SS |
| Rated Frequency (f) | Supply Circuit 50 Hz Supply Circuit 60 Hz |
| Rated Operational Current AC-15 (I_{θ}) | (24 / 127 V) 1.5 A (220 / 240 V) 1 A |
| Rated Operational Current DC-13 (I_{θ}) | (24 V) 0.3 A (125 V) 0.2 A |
| RoHS Date | 0626 5 |
| Sub-Function | 2-position |

Certificates and Declarations (Document Number)

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SFC151005C0201 |
| Declaration of Conformity - CE | 1SFA1-70 |
| Environmental Information | 1SFC151009D0201 |
| Instructions and Manuals | 1SFC151005C0201 |
| RoHS Information | 1SFC151012D0202 |

Classifications

| | |
|----------------------------|------------------------------------------------------------|
| E-nummer | 3705541 |
| ETIM 4 | EC002024 - Accessories for control circuit devices |
| ETIM 5 | EC001029 - Selector switch, complete |
| ETIM 6 | EC001029 - Selector switch, complete |
| Object Classification Code | S |
| UNSPSC | 39121500 |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categories

Low Voltage Products and Systems → Control Products → Pilot Devices → Pilot Devices - Compact Range

