

# Installation Accessories

## Handles



NPT	Poly Handle	Cable Range	Extended Handle	Nylon Handle	Angled Handle
1/2"	61-1A013-12	.20 - .83	61-1A413	-	-
3/4"	61-1A013-34	.31 - .59	-	61-1A013	-
1"	61-1A013-1	.32 - .67	-	-	61-1A313

**Notes:**

- Finger draw plates are recommended for easier connector closure on cord to cord assemblies.
- For available cord grips, see pgs 167-168.

- For a guideline of NPT sizes based on cable ranges, see DSN3 on pg 26.

## Angles



Nylon 30° Angle	Metal 30° Angle	Metal Straight Adapter - Inlet	Metal Straight Adapter - Receptacle
61-1A027	MA1	MSPN	MS1

## Junction Boxes



NPT	Metal Box	Metal Box with Nylon Angle	Poly* Conduit Entry
1/2"	MB312-601	61-1A053-080-12	61-1A023-12
3/4"	MB334-601	61-1A053-080-34	61-1A023-34
1"	MB31-601	61-1A053-080-1	-
1 1/4"	MB3114-601	61-1A053-080-114	-

\* For poly devices only

## Miscellaneous Accessories



\* Set of Two (2)



For Male Devices Only



For Male Devices Only

Finger Drawplates	Protective Cap	Padlockable Plug Cap
61-1A346	61-1A126	61-1A826

\* Recommended for cord to cord assembly applications, for easier connector closure

## Specialty Products Spotlight


### Voltage Phase Rotation Meter



Voltage phase rotation meter assemblies offer an easy means of testing Meltric receptacles for voltage and motor rotation. See pg 169.

## Order Example

A typical order should include an inlet part number, a receptacle part number **AND** the matching handles, angles or other required accessories.



Male Inlet with Handle (Plug)  
63-18043 + 61-1A013



Female Receptacle with Angle Adapter  
63-14043 + 61-1A027