







## Covers and Gaskets for Form 35® Unilet® Conduit Outlet Bodies




Covers Furnished with Stainless Steel Fastening Screws.

**Appleton Form 35® Covers and Gaskets** NOTE: Refer to page A-16 for Wiring Capacity Tables.

| Size                          | Blank Stamped Steel  | Blank Cast Malleable  | Neoprene   | Composition Fiber   |
|-------------------------------|--|---|--|---|
| Form 35<br>Body<br>Size (in.) | <br>Domed: 1/2" - 3"  | <br>Flat: 1/2" - 2"    | <br>Tear out<br>inner perforated<br>section to convert to<br>"open type" gasket. |  |
|                               | <br>Flat: 3-1/2" - 6" | <br>Domed: 2-1/2" - 4" |  |   |
| 1/2                           | K50  | K50-CM  | GK50-N   | GK50-V  |
| 3/4                           | K75  | K75-CM  | GK75-N   | GK75-V  |
| 1                             | K100   | K100-CM   | GK100-N  | GK100-V   |
| 1-1/4                         | K125 & 150   | K125 & 150-CM   | GK125-150-N  | GK125-150-V   |
| 1-1/2                         | K125 & 150   | K125 & 150-CM   | GK125-150-N  | GK125-150-V   |
| 2                             | K200   | K200-CM   | GK200-N  | GK200-V   |
| 2-1/2                         | K250 & 300   | K250 & 300-CM   | GK250-300-N  | GK-250-300-V  |
| 3                             | K250 & 300   | K250 & 300-CM   | GK250-300-N  | GK-250-300-V  |
| 3-1/2                         | K350 & 400   | K350 & 400-CM   | GK350-400-N  | GK-350-400-V  |
| 4                             | K350 & 400   | K350 & 400-CM   | GK350-400-N  | GK-350-400-V  |
| 5                             | K500   | —   | GK500-SN†  |   |
| 6                             | K600   | —   | GK600-SN†  |   |

† Not perforated

### Wiring Device Covers

|  |   |   |
|--|---|---|
|                 |                        |                                |
| <b>Lamp Receptacle</b> with<br>1-1/2" Shade Holder Groove.<br>Porcelain, 600 Watt, 600 Volt Rating | <b>Device Cover</b> for Interchangeable<br>(Despard) Wiring Devices,<br>Cast Aluminum with Mounting Strap | <b>Switch Cover</b> for Interchangeable<br>(Despard) Devices, Cast Aluminum<br>with Gasket and Steel Mounting Strap |
| <b>Form 35<br/>Body Size (in.)</b> <b>Cat. No.</b>   | <b>Form 35<br/>Body Size (in.)</b> <b>Cat. No.</b>  | <b>Form 35<br/>Body Size (in.)</b> <b>Cat. No.</b>  |
| 1/2 <b>KLR50</b>   | 1/2 <b>KWD50-A</b>  | 3/4 <b>KVS75-A</b>  |
| 3/4 <b>KLR75</b>   |   |   |