

# Rittal – The System.

Faster – better – everywhere.

## Wallmounted enclosure

Date : Oct 29, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Wallmounted enclosure – WM 1244.250 - WM161608NC

: 29.10.2019 build on [www.rittal.com/ca-en](http://www.rittal.com/ca-en)



## Product description

<b>Material:</b>	Door: Carbon steel, all-round foamed-in PU seal Housing: Carbon steel
<b>Surface finish:</b>	Housing and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting plate: Zinc-plated
<b>Color:</b>	RAL 7035
<b>Protection category IP to IEC 60 529:</b>	IP 66
<b>Protection category NEMA:</b>	NEMA 4
<b>Supply includes:</b>	Housing with door(s) Door hinged on left Mounting plate Rear wall mounting holes Quarter turn latch with slotted head insert

## Product features

<b>Dimensions:</b>	Height: 400 mm (16 ") Width: 400 mm (16 ") Depth: 210 mm (8.3 ")
<b>Material thickness::</b>	Housing: 1.5 mm (0.06 ") Door: 1.5 mm (0.06 ") Mounting plate: 1.5 mm (0.06 ")
<b>Mounting plate:</b>	Height: 375 mm (15 ") Width: 354 mm (14 ")

<b>Packaging unit:</b>	1 pc(s).
<b>Weight/packaging unit:</b>	10 kg (22 lb.)
<b>EAN:</b>	83113
<b>Approvals</b>	
<b>Approvals:</b>	UL + C-UL