



## Sealtite Type HCX: Extreme Temperature Flexible Conduit

Trade Size	Item ID	Std. Pkg. M (FT)	Inside Diameter Min	Outside Diameter		Bend Diameter	Weight Kg/m (lbs/cft)
				Min	Max		
3/8" (12)	39102	30 (100)	12.32 (0.485)	17.53 (0.690)	18.03 (0.710)	101 (4.0)	0.31 (21)
1/2" (16)	39112	30 (100)	15.75 (0.620)	20.83 (0.820)	21.34 (0.840)	127 (5.0)	0.37 (25)
3/4" (21)	39122	30 (100)	20.70 (0.815)	26.16 (1.030)	26.67 (1.050)	152 (6.0)	0.58 (39)
1" (27)	39131	30 (100)	26.16 (1.030)	32.77 (1.290)	33.40 (1.315)	203 (8.0)	0.76 (51)
1-1/4" (35)	39141	15 (50)	34.80 (1.370)	41.53 (1.635)	42.16 (1.660)	229 (9.0)	0.98 (66)
1-1/2" (41)	39151	15 (50)	40.01 (1.575)	47.37 (1.865)	48.26 (1.900)	279 (11.0)	1.55 (104)
2" (53)	39161	15 (50)	51.31 (2.020)	59.44 (2.340)	60.33 (2.375)	355 (14.0)	2.02 (136)

All dimensions in mm (inches)



**Square Lock Design** with cord packing 1/4" thru 1-1/4"



**Interlocked Design** 1-1/2" thru 2"

### SPECIFICATIONS:

- Galvanized steel core with Liquid-tight TPE jacket
- Colour: Black
- Temp. range: -60°C to +150°C (-65°F to +302°F)
- UV (sunlight) Resistant
- Extra Corrosion Resistant
- Oil Resistant

### Sealtite Type HCX:

**RoHS**

- Flexible metal core liquid-tight conduit
- Designed for extreme temperature applications where superior resistance to temperature ranges is required. (-60°C to +150°C)
- Available standard in Black.
- Uses standard liquid-tight connectors for easy installation.

For connectors for this conduit, see page 19-20  
For cutting instructions, see page 37

### APPLICATIONS:

- Extreme duty applications
- Extreme high or low temperature requirements
- Applications where no approvals are required