


## Industrial grade 50A locking devices

### Product description


3-pole, 4-wire grounding  
50A, 250V/DC / 600V/AC  
Non-NEMA



7765EX



7764EX



7968

### Industrial grade plugs & connectors

| A  | Rating V/DC | V/AC | Description    | Cord diameter            | Color   | Plug catalog no. | Connector catalog no. |  |  |
|----|-------------|------|----------------|--------------------------|---------|------------------|-----------------------|--|--|
| 50 | 250         | 600  | Pro grip nylon | 0.44-1.06" (11.1-26.0mm) | RD & BK | □ 7765EX*        | □ 7764EX*             |  |  |
|    |             |      | Armored        | 0.68-1.13" (17.3-28.6mm) | Steel   | □ 7765*          | □ 7764*               |  |  |

\*For replacement use in existing installations only

### Industrial grade receptacles

| A  | Rating V/DC | V/AC | Description | Color | Single receptacle |  |  |
|----|-------------|------|-------------|-------|-------------------|--|--|
| 50 | 250         | 600  | Receptacles | BK    | □ 7379*           |  |  |

\*For replacement use in existing installations only

### Industrial grade flanged inlets

| A  | Rating V/DC | V/AC | Description    | Color | Flanged inlet | Flanged inlet w/ lid |  |  |
|----|-------------|------|----------------|-------|---------------|----------------------|--|--|
| 50 | 250         | 600  | Flanged inlets | Steel | □ 7958*       | □ 7968*              |  |  |

\*For replacement use in existing installations only

### Accessories for 50A industrial grade locking devices

| Description  | Color suffix | Catalog no. |  |  |
|--|--------------|-------------|--|--|
| Weather protective glass-filled nylon, w/ lift lid cover | BK, CR, GY   | □ 7788_     |  |  |
| Weather protective diecast aluminum, w/ lift lid cover   |              | □ 7770      |  |  |
| Weather protective boot for 50A armored plug             |              | □ 7716      |  |  |
| Weather protective boot for 50A armored connector        |              | □ 7717      |  |  |
| Weather protective boot for 50A pro grip plug            |              | □ 7716EX    |  |  |
| Weather protective boot for 50A pro grip connector       |              | □ 7717EX    |  |  |



7788CR  
Corrosion resistant



7770



7716



7717



7716EX



7717EX

**Dimensional information:**  
C-80, C-81

**Plug & connector specification information:**  
50A: C-92

**Receptacle specification information:**  
50A: C-92

**Flanged inlet & flanged outlet specification information:**  
50A: C-92

### Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: BK (Black), GY (Gray), RD (Red), Y or CR (Yellow)



Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-32

RoHS compliant - Page Q-32