

Description:

- Low Voltage UL Power Fuse
- Type Class RK1
- Characteristics Time Delay
- Voltage Rating 600 VAC/VDC
- Current Rating 20 Ampere
- Interrupting Rating 200 Kiloampere (AC), 100 Kiloampere (DC)
- Terminal Type Ferrule
- Diameter 13/16 Inch
- Length 5 Inch
- Approval UL 248/248-12, CSA C22.2
- Body Material Polyester
- Contact Material Tin Plated Copper
- Mounting Clip
- Application Motor, Safety Switches, Transformers, Disconnects, Control Panels, All General Purpose Circuits

Features / Benefits

- Solid State Smartspot Visual Blown Fuse Indicator
- Time-Delay for Motor Starting and Transformer Inrush Currents without Nuisance Opening
- Extremely Current Limiting for Low Peak Let-Thru Current
- Recommended for Arc Flash Energy Reduction
- Easy 2-to-1 Selectivity for Prevention of Nuisance Shutdowns and "Blackouts"
- Rejection Style Design Prevents Replacement Errors When Used with Recommended Fuse Blocks
- High-Visibility Orange Label Gives Instant Brand Recognition
- Reduced Inventory by Taking the Place of Class RK5, K and H Fuses
- Metal-Embossed Date and Catalog Number for Easier Traceability and Lasting Identification
- Fiberglass Body Provides Dimensional Stability in Harsh Industrial Environments

UPC: 78200199184

Part Number: A6D20R