

# Brighten



Application illustration only, subject lamps not used in photo.

## LED commercial indoor/outdoor PAR38 lamps

For indoor and outdoor applications, GE offers a multitude of wattage options with a high light output.

### LOW-COST OPERATION

- For example, using only 26 watts of energy, save over \$517 in energy costs over the rated life of the lamp versus a standard 120-watt halogen lamp based on \$0.11 per kWh
- Energy efficiency and long life mean fewer lamp replacements versus standard incandescent and halogen light sources
- Ideal for both indoor and outdoor applications
- UL wet rated for outdoor applications

### EXCELLENT COLOR RENDERING

- Available with a CRI of 82 - 84

### COLOR TEMPERATURE

- Halogen-like color
- Available in 2500K, 2700K, 3000K, 3500K, 4000K and 5000K

### LONG LIFE

- Up to 25,000 hours rated life (L70)

### DIMMABLE

- Dims from 100% to 10%

### BEAM PATTERNS

- Available in 12°, 15°, 25°, 35° and 40° beam patterns

### ENVIRONMENTALLY CONSCIOUS

- These lamps are energy efficient and contain no lead or mercury

### GE QUALITY AND RELIABILITY

- 3-year limited warranty

ecomagination<sup>SM</sup>

To learn more about saving money and energy, go to: <http://products.currentbyge.com>.



Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

**current**  
powered by GE




# LED commercial indoor/outdoor PAR38 lamps


## Directional Lamps (PAR)

| Bulb Shape   | Base Type | Watts | Order Code | Description       | Volts | Case Qty** | MOL (In) | Lumens Initial | CBCP  | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information        |  |
|--|-----------|-------|------------|-------------------|-------|------------|----------|----------------|-------|--------------------|-----|---------------------|-----------------------|----------|---------------------|------------------|-------------------------------|--|
| <b>PAR38 - Low Glare - Visual Comfort Lens™</b>                                  |           |       |            |                   |       |            |          |                |       |                    |     |                     |                       |          |                     |                  |                               |  |
|  | MED       | 12    | 92971      | LED12D38W3827/40  | 120   | 6          | 5.31     | 1050           | 2300  | 2700               | 81  | 100W                | 25,000                | Yes      | ★                   | Damp             | Flood, 40° beam, White        |  |
|  |           |       | 92972      | LED12D38W3830/25  | 120   | 6          | 5.31     | 1050           | 5500  | 3000               | 81  | 100W                | 25,000                | Yes      | ★                   | Damp             | Narrow Flood, 25° beam, White |  |
|  |           |       | 92973      | LED12D38W3830/40  | 120   | 6          | 5.31     | 1050           | 2300  | 3000               | 80  | 100W                | 25,000                | Yes      | ★                   | Wet              | Flood, 40° beam, White        |  |
|  | 18        |       | 92950      | LED18D38OW3827/25 | 120   | 6          | 5.12     | 1550           | 5800  | 2700               | 81  | 120W                | 25,000                | Yes      | ★                   | Wet              | Narrow Flood, 25° beam, White |  |
|  |           |       | 92923      | LED18D38W3927/25  | 120   | 6          | 5.31     | 1250           | 4900  | 2700               | 92  | 100W                | 25,000                | Yes      | ★                   | Damp             | Narrow Flood, 25° beam, White |  |
|  |           |       | 92958      | LED18D38OW3827/40 | 120   | 6          | 5.12     | 1550           | 3800  | 2700               | 81  | 120W                | 25,000                | Yes      | ★                   | Wet              | Flood, 40° beam, White        |  |
|  |           |       | 92926      | LED18D38W3927/40  | 120   | 6          | 5.12     | 1250           | 2900  | 2700               | 92  | 120W                | 25,000                | Yes      | ★                   | Damp             | Flood, 40° beam, White        |  |
|  |           |       | 92927      | LED18D38W3930/15  | 120   | 6          | 5.32     | 1350           | 15000 | 3000               | 92  | 75W                 | 25,000                | Yes      | ★                   | Wet              | Spot, 15° beam, White         |  |
|  |           |       | 92961      | LED18D38W3830/15  | 120   | 6          | 5.12     | 1750           | 20000 | 3000               | 81  | 150W                | 25,000                | Yes      | ★                   | Wet              | Spot, 15° beam, White         |  |
|  |           |       | 92963      | LED18D38OW3830/25 | 120   | 6          | 5.12     | 1550           | 6000  | 3000               | 81  | 120W                | 25,000                | Yes      | ★                   | Wet              | Narrow Flood, 25° beam, White |  |
|  |           |       | 92933      | LED18D38W3930/25  | 120   | 6          | 5.31     | 1350           | 5200  | 3000               | 92  | 100W                | 25,000                | Yes      | ★                   | Damp             | Narrow Flood, 25° beam, White |  |
|  |           |       | 92967      | LED18D38OW3830/40 | 120   | 6          | 5.12     | 1550           | 4000  | 3000               | 81  | 150W                | 25,000                | Yes      | ★                   | Wet              | Flood, 40° beam, White        |  |
|  |           |       | 92934      | LED18D38W3930/40  | 120   | 6          | 5.12     | 1350           | 3200  | 3000               | 92  | 120W                | 25,000                | Yes      | ★                   | Damp             | Flood, 40° beam, White        |  |
|  |           |       | 85085      | LED18D38OW3835/25 | 120   | 6          | 5.31     | 1700           | 6500  | 3500               | 81  | 120W                | 25,000                | Yes      | ★                   | Wet              | Narrow Flood, 25° beam, White |  |
|  |           |       | 87917      | LED18D38OW3835/40 | 120   | 6          | 5.31     | 1700           | 4400  | 3500               | 81  | 150W                | 25,000                | Yes      | ★                   | Wet              | Flood, 40° beam, White        |  |
|  |           |       | 93171      | LED18D38OW3840/25 | 120   | 6          | 5.31     | 1700           | 6500  | 4000               | 81  | 120W                | 25,000                | Yes      | ★                   | Wet              | Narrow Flood, 25° beam, White |  |
|  |           |       | 93172      | LED18D38OW3840/40 | 120   | 6          | 5.31     | 1700           | 4400  | 4000               | 81  | 150W                | 25,000                | Yes      | ★                   | Wet              | Flood, 40° beam, White        |  |
|  |           |       | 65730      | LED18D38OW3850/25 | 120   | 6          | 5.31     | 1700           | 6500  | 5000               | 81  | 120W                | 25,000                | Yes      | ★                   | Wet              | Narrow Flood, 25° beam, White |  |
|  |           |       | 65731      | LED18D38OW3850/40 | 120   | 6          | 5.31     | 1700           | 4400  | 5000               | 81  | 150W                | 25,000                | Yes      | ★                   | Wet              | Flood, 40° beam, White        |  |

## Directional Lamps (PAR38 - High Output)

| Bulb Shape  | Base Type | Watts | Order Code | Description      | Volts   | Case Qty** | MOL (In) | Lumens Initial | CBCP   | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information        |  |
|---|-----------|-------|------------|------------------|---------|------------|----------|----------------|--------|--------------------|-----|---------------------|-----------------------|----------|---------------------|------------------|-------------------------------|--|
| <b>Single Optics</b>  |           |       |            |                  |         |            |          |                |        |                    |     |                     |                       |          |                     |                  |                               |  |
|  |           | 32    | 75447      | LED32DP38W830/15 | 120     | 6          | 5.12     | 3000           | 26,000 | 3000               | 82  | 250W                | 25,000                | Yes      | ★                   | Wet              | Spot, 15° beam, White         |  |
|   |           |       | 88801      | LED32DP38W830/25 | 120     | 6          | 5.12     | 3000           | 13,000 | 3000               | 80  | 250W                | 25,000                | Yes      | ★                   | Wet              | Narrow Flood, 25° beam, White |  |
|   |           |       | 88810      | LED32DP38W830/40 | 120     | 6          | 5.12     | 3000           | 6,000  | 3000               | 80  | 250W                | 25,000                | Yes      | ★                   | Wet              | Flood, 40° beam, White        |  |
|   |           |       | 30233      | LED32DP38W835/15 | 120     | 6          | 5.12     | 3100           | 25000  | 3500               | 80  | 250W                | 25,000                | Yes      | ★                   | Wet              | Spot, 15° beam, White         |  |
|   |           |       | 30237      | LED32DP38W835/25 | 120     | 6          | 5.12     | 3100           | 13000  | 3500               | 80  | 250W                | 25,000                | Yes      | ★                   | Wet              | Narrow Flood, 25° beam, White |  |
|   |           |       | 30239      | LED32DP38W835/40 | 120     | 6          | 5.12     | 3100           | 6000   | 3500               | 80  | 250W                | 25,000                | Yes      | ★                   | Wet              | Flood, 40° beam, White        |  |
|   |           |       | 20109      | LED32P38W830/15  | 120-277 | 6          | 5.12     | 3000           | 25000  | 3000               | 80  | 250W                | 25,000                | -        | -                   | Wet              | Coming Soon                   |  |
|   |           |       | 20130      | LED32P38W830/25  | 120-277 | 6          | 5.12     | 3000           | 13000  | 3000               | 80  | 250W                | 25,000                | -        | -                   | Wet              | Coming Soon                   |  |
|   |           |       | 20137      | LED32P38W830/40  | 120-277 | 6          | 5.12     | 3000           | 6000   | 3000               | 80  | 250W                | 25,000                | -        | -                   | Wet              | Coming Soon                   |  |

## Directional Lamps (PAR38- Value)

| Bulb Shape   | Base Type | Watts | Order Code | Description | Volts            | Case Qty** | MOL (In) | Lumens Initial | CBCP | Initial Color Temp | CRI  | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information       |                              |
|--|-----------|-------|------------|-------------|------------------|------------|----------|----------------|------|--------------------|------|---------------------|-----------------------|----------|---------------------|------------------|------------------------------|------------------------------|
| <b>Single Optics</b>   |           |       |            |             |                  |            |          |                |      |                    |      |                     |                       |          |                     |                  |                              |                              |
|  | PAR38     | MED   | 11         | 91360       | LED11P38W830/25  | 120        | 6        | 5.04           | 950  | 4000               | 3000 | 90W                 | 10,000                | -        | -                   | Wet              | Flood, 25° beam, White, STIR |                              |
|  |           |       | 15         | 32213       | LED15DP38W830/40 | 120        | 6        | 5.04           | 1300 | 2300               | 3000 | 81                  | 90W                   | 25,000   | Yes                 | ★                | Wet                          | Flood, 40° beam, White, STIR |

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

\* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

\*\* Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★ are not ENERGY STAR® certified.

# UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "TTP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.



Product is compliant with material restriction requirements of RoHS

ENERGY STAR® and the ENERGY STAR® logo are registered U.S. marks



<http://products.currentbyge.com>

GE and the GE Monogram are trademarks of the General Electric Company. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company. © 2018 GE.

63555 (Rev 01/29/18)

