

## SINGLE PHASE, NEMA 3R STYLE ENCLOSURE



**600 Primary Volts**

**12/24 Secondary Volts**

**60 Hz**

VA Rating	Catalog Number	Case Style (Page 228)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall	Wiring Diagram (Page 240)
			Width	Depth	Height			
50	<b>QC05PRCB</b>	NQ0	3.69	5.06	7.19	6	W	SCD 4
100	<b>QC10PRCB</b>	NQ0	3.69	5.06	7.19	7	W	SCD 4
150	<b>QC15PRCB</b>	NQ0	3.69	5.06	7.19	8	W	SCD 4
200	<b>QC20PRCB</b>	NQ1	4.31	5.56	7.19	11	W	SCD 4
250	<b>QC25PRCB</b>	NQ1	4.31	5.56	7.19	13	W	SCD 4
350	<b>QC35PRCB</b>	NQ1	4.31	5.56	7.19	14	W	SCD 4
500	<b>QC50PRCB</b>	NQ2	5.06	4.56	9.30	15	W	SCD 4
750	<b>QC75PRCB</b>	NQ2	5.06	4.56	9.30	18	W	SCD 4
1000	<b>Q1C0PRCB</b>	NQ3	5.88	5.19	10.56	25	W	SCD 4
1500	<b>Q1C5PRCF</b>	NQ4	7.06	6.25	11.75	36	W	SCD 4
2000	<b>Q002PRCF</b>	NQ4	7.06	6.25	11.75	46	W	SCD 4
3000	<b>Q003PRCF</b>	NQ4	7.06	6.25	11.75	65	W	SCD 4
5000	<b>Q005PRCF</b>	NQ5	10.00	7.75	17.25	105	W	SCD 4

SECTION 1

